



# Data - MRL Range

## DATA - MRL (Machine Room-Less) Passenger Lift Range

The data below only reflects our *most common* sizes and configurations (at a speed of 1m/s). Further sizes and speeds are available so if you do not find what you are looking for, please ask. Note: 2PSO= 2 Panels Side Opening, 2PCO= 2 Panels Centre Opening, 3PSO= 3 Panels Side Opening.

LOAD	ENTRANCE LAYOUT	INTERNAL SHAFT DIMENSIONS		CAR SIZE (at a height of 2100mm)		DOOR TYPES	DOORS OPENING (at 2000mm height)	PIT	HEADROOM
		WIDTH (mm)	DEPTH (mm)	WIDTH (mm)	DEPTH (mm)		WIDTH (mm)		
300 / 4	Single	1450	1400	840	1100	2PSO Automatic	700	1100	3450
450 / 6	Single	1550	1550	1000	1200	2PSO Automatic	800	1100	3450
450 / 6	Through (180°)	1550	1650	1000	1200	2PSO Automatic	800	1100	3450
450 / 6	Adjacent (90°)	1700	1550	1000	1200	2PSO Automatic	800	1100	3450
630 / 8	Single	1650	1650	1100	1400	2PSO Automatic	800 / 900	1100	3450
630 / 8	Through (180°)	1650	1750	1100	1400	2PSO Automatic	800 / 900	1100	3450
630 / 8	Adjacent (90°)	1810	1700	1100	1400	2PSO Automatic	800 / 900	1100	3450
800 / 10	Single	1750	1900	1100	1600	2PSO Automatic	900	1200	3450
800 / 10	Through (180°)	1750	2050	1100	1600	2PSO Automatic	900	1200	3450
800 / 10	Adjacent (90°)	1860	2000	1100	1600	2PSO + 3PSO Automatic	900	1200	3450
1000 / 13	Single	1750	2400	1100	2100	2PSO Automatic	900	1200	3450
1000 / 13	Through (180°)	1750	2550	1100	2100	2PSO Automatic	900	1200	3450
1000 / 13	Single	2350	1900	1600	1400	2PCO Automatic	900	1200	3450
1000 / 13	Through (180°)	2350	1815	1600	1400	2PCO Automatic	900	1200	3450
1250 / 16	Single	1900	2600	1200	2300	2PSO Automatic	1100	1200	3450
1250 / 16	Through (180°)	1900	2750	1200	2300	2PSO Automatic	1100	1200	3450
1275 / 17	Single	3000	1900	2020	1410	2PSO / 2PCO Automatic	1100	1300	3600
1275 / 17	Through (180°)	3000	1900	2020	1410	2PSO / 2PCO Automatic	1100	1300	3600
1350 / 18	Single	2200	2800	1200	2500	2PSO Automatic	1100	1300	3600
1350 / 18	Through (180°)	2200	2950	1200	2500	2PSO Automatic	1100	1300	3600
1500 / 20	Single	2300	2700	1300	2400	2PSO Automatic	1100	1300	3600
1500 / 20	Through (180°)	2300	2850	1300	2400	2PSO Automatic	1100	1300	3600
1600 / 21	Single	2400	2700	1400	2400	2PSO Automatic	1100	1300	3600
1600 / 21	Through (180°)	2400	2850	1400	2400	2PSO Automatic	1100	1300	3600
1600 / 21	Adjacent (90°)	2260	2750	1400	2400	2PSO Automatic	1100	1300	3600
2000 / 26	Single	2500	3000	1500	2700	2PSO Automatic	1100	1300	3600
2000 / 26	Through (180°)	2500	3150	1500	2700	2PSO Automatic	1100	1300	3600
2500 / 33	Single	2600	3350	1600	3000	2PSO Automatic	1400	1400	3700
2500 / 33	Through (180°)	2600	3500	1600	3000	2PSO Automatic	1400	1400	3700
2900 / 38	Single	2800	3350	1800	3000	2PSO Automatic	1400	1400	3700
2900 / 38	Through (180°)	2800	3500	1800	3000	2PSO Automatic	1400	1400	3700

Note – all details are correct at time of compilation, however all data maybe subject to change without prior notice at any time.