

# THE *Goodsmaster*

GOODS LIFTS RANGE  
500 - 1500kg



*GIVING ROBUST AND  
DEPENDABLE FLOOR TO FLOOR  
MOVEMENT OF GOODS*

# Goodsmaster

## GOODS LIFTS

### ● Choice of five models

Whether you are lifting palletised goods, large roll containers, warehouse stock, furniture or bulky goods, heavy electrical or industrial equipment, trolleys, sack barrows or washing machines, you can choose from five models with 500kg, 750kg, 1000kg or 1500kg capacity to suit your exact lifting requirements.

### ● Quick, simple installation

The Goodsmaster operates inside a rapidly-erected, structure supported framework which is easy to install virtually anywhere and requires minimal builder's work. No separate motor room or load-bearing wall or lift shaft is needed, which helps to keep costs down.

### ● Quick delivery

All the Goodsmaster models can be delivered in a few weeks and can be installed and working within a few days.

### ● Easy handling

Up to two-way entry (single or through car) on every floor to give most convenient access positions.

### ● Entrances

A single hinged steel door is supplied as standard on 1045mm wide lift cars. Double hinged steel doors are supplied as standard on 1305mm and 1445mm wide lift cars. All are finished in grey baked enamel. Collapsible concertina gates are available as an option on all models.

### ● Car entrance

A collapsible gate is fitted to the lift car entrance as standard.

### ● Lift enclosure

Sheet steel motor-room cabinet and shaft cladding (non fire rated) available as an optional extra.



Double hinged steel door on 1305 and 1445mm wide cars

- Large Roll Containers
- Furniture/Bulk
- Heavy Industrial Equipment
- Sack Barrows



- 1 Robust push buttons, fully automatic control
- 2 Grey baked enamel framework for long life
- 3 Electronically interlocked hinged steel doors
- 4 Easy-clean finish
- 5 Collapsible gate
- 6 Quiet and efficient powerful motor
- 7 Structure supported frame
- 8 Low pit or optional ramp
- 9 Concertina gate (optional)

# Goodsmaster

GOODS LIFTS 500 - 1500kg

## BRIEF SPECIFICATION:

|                                 |  |
|---------------------------------|--|
| <b>Load:</b>                    | 500kg, 750kg, 1,000kg and 1,500kg.   |
| <b>Car:</b>                     | Constructed from mild steel sheeting, finished in a tough grey baked enamel with heavy duty vinyl covered floor.   |
| <b>Landing Entrances:</b>       | Single hinged steel door on 1045mm wide lift cars. Double hinged steel doors on 1305 and 1445mm wide lift cars. Finished in grey baked enamel, or optional galvanised concertina gate.   |
| <b>Car Entrance Protection:</b> | A collapsible gate is fitted to the lift car entrance(s) as standard.  |
| <b>Mounting:</b>                | The Goodsmaster is supplied in a structure supported frame. A solid base and support at each floor is all that is needed from your building.   |
| <b>Floors Served:</b>           | Up to 4 stops.   |
| <b>Speed:</b>                   | 0.20m/s nominal.   |
| <b>Travel:</b>                  | Up to 12 metres of travel.   |
| <b>Entry Choice:</b>            | Up to two entrances can be fitted on each floor.   |
| <b>Control:</b>                 | Fully automatic push button control with call and despatch facilities at each landing entrance.  |
| <b>Indicators:</b>              | "Lift arrival" and "lift occupied" indicators are fitted at each entrance for extra reassurance, together with an audible lift arrival buzzer.   |
| <b>Motor/Winding Unit:</b>      | Mounted on a bedplate fixed to the lift's structure. The motor drives a high quality reduction gearbox with 2:1 traction roping. Efficient and quiet in operation.   |
| <b>Electric Supply:</b>         | 380/415 Volt - 50Hz - 3 phase. A good earth but no neutral is required. A 15 amp isolator adjacent to the motor should be supplied for the lift by your electrician. For details, please ask for our builders work folder.   |
| <b>Installation:</b>            | A 2-floor Goodsmaster normally takes a few days to install, depending on site conditions. Once the builder's work has been completed we then return to site to commission, test and 'CE' mark the lift. At this stage we will show you how to use the lift properly. |
| <b>Delivery:</b>                | A few weeks - please ask for details.  |
| <b>Enclosure:</b>               | Available as an option (not fire rated).   |
| <b>Maintenance:</b>             | We recommend the Goodsmaster is serviced and inspected every 3 months by competent lift engineers. This is to ensure efficient and reliable operation. We can arrange servicing after installation.  |
| <b>Guarantee:</b>               | The Goodsmaster is guaranteed for twelve months from completion of installation, subject to it being serviced regularly by our engineers.  |
| <b>Policy:</b>                  | We are continually developing and improving the Goodsmaster range and reserve the right to alter specifications, dimensions and prices without prior notice .  |
| <b>Safety:</b>                  | Once installed, tested, commissioned and all the building work is complete, the Goodsmaster will comply with the Essential Safety Regulations (ESRs) of the Supply of Machinery (Safety) Regulations 1992, otherwise known as the Machinery Directive.               |
| <b>Optional Extras:</b>         | • Intercom system positioned at each landing entrance • Motor room enclosure • Sheet steel cladding finished in grey baked enamel • 1800mm high lift car • Shutter leaf landing gates  |



## LANDMARK LIFTS LTD

29 CHARTER GATE, QUARRY PARK CLOSE, MOULTON PARK,  
NORTHAMPTON NN3 6QB

t 0800 652 8138 f 01604 495 111 e info@landmarklifts.co.uk

[www.landmarklifts.co.uk](http://www.landmarklifts.co.uk)

Note - all details are correct at time of completion, however, all data may be subject to change without prior notice. These details cannot form part of a written contract